



## Security Conditions and Requirements of the Manufacture and Sale of Precious Metals and Stones

Version No: 4.0

Release Date: 14/02/2022

Version Notes: updating the presentation of requirements, in addition to listing the issued amendments based on the initiative of reducing the government requirements by 30%





## Chapter 1: Standard and Technical Specifications of the Security Systems

<u>Application of Standard and Technical Specifications of Security Systems of Law No. (12) of 2016, issued in February 2022, on regulating the Security Industry in Emirate of Dubai</u>





## **Chapter 2: Security Conditions and Requirements**

## Manufacture and Sale of Precious Metals and Stones:

The manufacture and sale of precious metals and stones include the following:

- 1. Trade in gold trade and fine jewelry;
- 2. Trade in metal alloys;
- 3. Trade in gold and silver jewelry;
- 4. Trade in pearls and precious stones;
- 5. Foundry of gold and precious metals;
- 6. Manufacture of jewelry made of gold and precious metals;
- 7. Manufacture of precious jewelry;
- 8. Jeweler of gold and precious jewelry;
- 9. Repair of jewelry, jewels and artefacts.

| Requirements of the Visual Surveillance System – VSS |  |   |  |
|--|--|---|--|
| S.N  | Requirement  | Description   | Remarks  |
| 1  | at all entrances of the establishment  | Identification View   |  |
| 2  | at all emergency exits   | Identification View   |  |
| 3  | at the display and sale tables   | Observation View  |  |
| 4  | at the Cashier   | Recognition View  |  |
| 5  | at the safe  | Recognition View  |  |
| 6  | at the display tables and<br>boxes that located outside<br>the establishment or<br>elsewhere | Recognition View  |  |
| 7  | at the external area of the establishment  | Monitoring View   | The camera's angle of view shall not be less than 110 degrees. |
| 8  | at the lobby   | Monitoring View   |  |
| 9  | Recording Devices<br>Accuracy  | Cameras resolution and recording devices accuracy shall not be less than Full HD1080p |  |



| 10 | Recording Mode  | The recording mode shall be set to at least ten frames per second (10fps) per camera.       |  |
|----|---|---|--|
| 11 | Duration of the<br>Recordings                           | The recordings shall be kept for at least 31 days for all cameras.                          |  |
| 12 | Uninterruptible power supply (UPS)                      | All cameras and recording devices shall be connected to uninterruptible power supply (UPS). |  |
| 13 | System of linking and following up the integrity of VSS | Installing a system for linking and following up the integrity of VSS                       |  |

| The Alarm System |                           |                                   |         |
|------------------|---------------------------|-----------------------------------|---------|
| S.N              | Requirement               | Description                       | Remarks |
| 1                | at the protected areas,   | All areas, including but not      |         |
|                  | offices and management    | limited to the protected areas,   |         |
|                  | areas connecting directly | offices and management areas      |         |
|                  | to the store.             | connecting directly to the        |         |
|                  |                           | store, shall be covered by        |         |
|                  |                           | sensors field so that there is no |         |
|                  |                           | zone that can be penetrated to    |         |
|                  |                           | disrupt or disable the security   |         |
|                  |                           | system.                           |         |
| 2                | The Glass Facades         | All glass facades of the          |         |
|                  |                           | establishment shall be            |         |
|                  |                           | equipped with glass break         |         |
|                  |                           | sensors or motion detectors.      |         |
| 3                | The Entrances and Exits   | The main and secondary            |         |
|                  |                           | entrances and emergency exits,    |         |
|                  |                           | if any, shall be equipped with    |         |
|                  |                           | magnetic keys.                    |         |
| 4                | The Safe                  | The safe shall be equipped        |         |
|                  |                           | with a seismic detector sensor    |         |
|                  |                           | or motion detector sensor.        |         |
| 5                | The Panic Button          | The cashier, seller and           |         |
|                  |                           | manager shall be provided         |         |
|                  |                           | with panic button to be used in   |         |
|                  |                           | case of any emergency. It must    |         |
|                  |                           | be at a level that is easily      |         |
|                  |                           | accessible and is not visible at  |         |
|                  |                           | the same time for the visitors.   |         |

| Other Requirements |                 |   |         |
|--------------------|-----------------|---|---------|
| S.N                | Requirement     | Description   | Remarks |
| 1                  | Security Guards | Security guards shall be provided during the official |         |



|   |                                | working hours for the locations containing pieces of art that are worth more than one million dirhams.   |  |
|---|--------------------------------|--|--|
| 2 | Fixed Iron Window Grill        | A fixed iron window grill shall be installed on all external vents (which are not in the display area such as the windows of service rooms, bathrooms and ventilation rooms).            |  |
| 3 | Iron Shutters                  | Iron shutters that are closed after<br>the official working hours shall<br>be installed.   | The iron shutters may be replaced by penetration-resistant glass       |
| 4 | Penetration-Resistant<br>Glass | Penetration-resistant glass or films installed on the outside frame shall be used on the glass facades of the establishment to prevent penetration of the glass for at least 90 seconds. | Penetration-resistant glass may<br>be replaced by the iron<br>shutters |
| 5 | Locks                          | Locks shall be installed and approved by SIRA.   |  |